

TELECOMMUNICATION NETWORK USING THE W-CDMA PROTOCOL WITH AAL-2 BASED TERMINATION POINTS

Patent number: EP1236374

Publication date: 2002-09-04

Inventor: BRUNDERT MARTIN (DE); CUADRADO CAPITAN FAUSTINO (DE); SOLANA DE QUESADA JUAN IGNACIO (DE)

Applicant: NOKIA CORP (FI)

Classification:


- international: **H04Q11/04**; H04L12/56; **H04Q11/04**; H04L12/56; (IPC1-7): H04Q11/04

- european: H04Q11/04S2

Application number: EP19990948893 19990929

Priority number(s): WO1999EP07210 19990929

Also published as:


 WO0124570 (A1)

Report a data error here


Abstract not available for EP1236374

Abstract of corresponding document: **WO0124570**

The invention concerns a telecommunication network using the W-CDMA protocol comprising a variety of base stations (BS) communicating with each other via a central Radio Network Controller (RNC) by an ATM based data connection via an IUB interface, whereby at least one of the base stations (BS) is comprising a variety of radio sectors (1, 2, 3, ...n) with physically distributed AAL-2 based termination points (TP), each termination point having an AAL-2 over ATM structure where different call IDs are mapped into respective ATM virtual connections (ATM/VC) under the control of a control unit timer (CU-timer) having a determined delay time, all AAL cell streams being sent parallel to each other to an ATM switching unit (AXU) via a UTOPIA interface. In order to increase the efficiency of the system without a reduction of the maximum allowed delay, the ATM switching unit comprises a multiplexing unit (AAM CPS MUX) for multiplexing AAL-2 connections of the different termination points (TP) into one single ATM virtual connection to be processed by the ATM switch.



Data supplied from the **esp@cenet** database - Worldwide



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11)

EP 1 236 374 A1

(43) Date of publication:
04.09.2002 Bulletin 2002/36

(21) Application number: 99948893.5

(22) Date of filing: 29.09.1999

(51) Int. Cl. ⁷: **H04Q 11/04**

(86) International application number:
PCT/EP99/07210

(87) International publication number:
WO 01/024570 (05.04.2001 Gazette 2001/14)

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(71) Applicant: **Nokia Corporation**
02150 Espoo (FI)

(72) Inventors:
• **BRUNDERT, Martin**
D-40474 Düsseldorf (DE)

• **CUADRADO CAPITAN, Faustino**
D-40880 Ratingen (DE)
• **SOLANA DE QUESADA, Juan, Ignacio**
D-40878 Ratingen (DE)

(74) Representative:
Cohausz & Florack
Patentanwalte
Kanzlerstrasse 8a
40472 Düsseldorf (DE)

(54) **TELECOMMUNICATION NETWORK USING THE W-CDMA PROTOCOL WITH AAL-2 BASED TERMINATION POINTS**

(87) This international application for which the EPO is a designated office has not been republished by the EPO according to article 158(1) EPC.

Cette demande internationale pour laquelle l'OEB est office d'origine n'a pas été republiée par l'OEB en vertu de l'article 158(1) CBE.

Diese internationale Anmeldung, für die das EPA Bestimmungsamt ist, wurde, gemäß Artikel 158(1) EP, vom EPA nicht wieder veröffentlicht.

EP 1 236 374 A1

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/24570 A1

- (51) International Patent Classification⁷: **H04Q 11/04** (74) Agent: **COHAUSZ & FLORACK**; Kanzlerstrasse 8a, D-40470 Düsseldorf (DE).
- (21) International Application Number: **PCT/EP99/07210** (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (22) International Filing Date:
29 September 1999 (29.09.1999)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (*for all designated States except US*): **NOKIA NETWORKS OY** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **BRUNDERT, Martin** [DE/DE]; Orsoyer Strasse 23, D-40474 Düsseldorf (DE). **CUADRADO CAPITAN, Faustino** [ES/DE]; Westtangente 15, D-40880 Ratingen (DE). **SOLANA DE QUESADA, Juan, Ignacio** [ES/DE]; Lohgerberstrasse 10, D-40878 Ratingen (DE).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **TELECOMMUNICATION NETWORK USING THE W-CDMA PROTOCOL WITH AAL-2 BASED TERMINATION POINTS**



(57) Abstract: The invention concerns a telecommunication network using the W-CDMA protocol comprising a variety of base stations (BS) communicating with each other via a central Radio Network Controller (RNC) by an ATM based data connection via an I_{UB} interface, whereby at least one of the base stations (BS) is comprising a variety of radio sectors (1, 2, 3, ...n) with physically distributed AAL-2 based termination points (TP), each termination point having an AAL-2 over ATM structure where different call IDs are mapped into respective ATM virtual connections (ATM/VC) under the control of a control unit timer (CU-timer) having a determined delay time, all AAL cell streams being sent parallel to each other to an ATM switching unit (AXU) via a UTOPIA interface. In order to increase the efficiency of the system without a reduction of the maximum allowed delay, the ATM switching unit comprises a multiplexing unit (AAM CPS MUX) for multiplexing AAL-2 connections of the different termination points (TP) into one single ATM virtual connection to be processed by the ATM switch.

WO 01/24570 A1

TELECOMMUNICATION NETWORK USING THE W-CDMA PROTOCOL WITH AAL-2 BASED TERMINATION POINTS

The present invention concerns telecommunication network using the W-CDMA protocol comprising a variety of base stations communicating with each other via a central Radio Network Controller by an ATM based data connection via an I_{UB} interface whereby at least one of the base stations is comprising a variety of radio sectors with physically distributed AAL-2 based termination points, each termination point having a AAL-2 over ATM structure where different call ID's are mapped into ATM virtual connections under the control of a control unit timer with a given delay time, all AAL cell streams being sent parallel to each other to an ATM switching unit via an UTOPIA interface.

Moreover, the invention concerns an ATM (= Asynchronous Transfer Mode) switch for a telecommunication network mentioned above as well as a method for processing data within a telecommunication network mentioned above.

The principal structure of a telecommunication network using the W-CDMA (Wideband-Code Division Multiple Access) protocol is known from practical knowledge. The structure and function of networks of that kind is known from ITU-T Recommendation I.362.2. Networks of this kind play on important role in the so called „Third Generation“ telecommunication networks.

- 2 -

These kinds of networks use the AAL-2 (= ATM Adaptation Layer) over ATM standards as the protocols for broadband transmission. There are usually a variety of different base stations within the W-CDMA network each of which defining a cell. A cell, especially a cell covering an area with dense traffic can be divided into a number of sectors. Each of the sectors contains its own termination point for the AAL over ATM data. To each call in a given sector of a base station a call identification (call ID, CID) is allocated and a number of calls within a given sector is mapped into a single ATM virtual connection under use of the call ID.

The multiplexing/mapping of the different calls into one single ATM virtual connection at the respective termination point is governed by a control unit. The control unit comprises a control unit timer (CU timer) which supervises the mapping of the calls into the ATM cell which has a given length (53 bits, were 48 bits are reserved for the payload). Each ATM cell is filled with the data coming from different calls within a given sector until the ATM cell is full or the allowed CU timer limit is achieved which means that the given CU time is expired. The reason for the timer is to guarantee a maximum delay in the process of filling up the ATM cells in case if there are not enough data from the calls to be transmitted. This means, if the CU timer time expires, when the ATM cell is not yet filled, the ATM cell is transmitted only partially filled which results in a reduced efficiency.

This means, that a small value of the CU timer has the advantage that only small delay in the process of filling up the ATM cells is achieved but, that the probability of generating only partially filled cells is increased.

- 3 -

On the other hand, if the CU timer is set to a larger value, the probability of generating only partially filled cells is reduced but this does not guarantee the required maximum delay time. In an extrapolation, if the time delay of the CU timer would be infinite, the probability of filling all cells is 100 percent, which would result in the best efficiency of the ATM network.

An other problem raising is that the amount of simultaneous calls that a single sector of a base station has to handle may not be enough to make the usage of the ATM bandwidth effective enough. Theoretical valuations have shown that the use of AAL-2 over ATM technology is only efficient if the number of CIDs in a single ATM virtual connection is at least 50.

It is therefore the object of the present invention to increase the efficiency of the telecommunication network without a drop of the required maximum delay time.

This object is achieved in a system mentioned above by the ATM switching unit comprising a multiplexing unit for multiplexing AAL-2 connections of the different termination points TP into one single ATM virtual connection to be processed by the ATM switch.

Accordingly, this object is achieved by a method for operating a network mentioned above by the parallel incoming ALL-2 connections of different termination points of one base station being multiplexed into one single ATM cell virtual connection before being processed by the ATM switch.

It is the central idea of the present invention to propose a system and a method to increase the bandwidth

- 4 -

usage efficiency by combining the parallel data traffic coming from different sectors of one base station before it is processed by the ATM switch. The incoming parallel data streams from the physically distributed termination points at the AAL-2 layer are multiplexed at a centralized location which leads to a very high efficiency because now - also for non-infinite delay times - the ATM virtual connections are processed with a very high occupancy rate. Nevertheless, the different sectors of the base station are still able to generate AAL-2 cells and transfer them to the multiplexing unit by using the standard UTOPIA interface. For all parallel data paths parts before the multiplexer, the CU time for mapping the AAL cells can be selected small so that low delay is guaranteed. Accordingly, at this part of the network the probability for partially filled cells is still large and a number of CID values used by the different BS sectors can still be small. After the multiplexing step, however, the number of CIDs used in the single ATM virtual connection is now significantly larger because the data stream combines all calls coming from different sectors of the base station. This means that the „dummy information“ which was contained in the AAL cells at the UTOPIA interface before the multiplexing operation is removed by which the efficiency of the whole system is remarkably enhanced.

A preferred embodiment of the system is characterized in that both the AAL-2 stream coming from the individual radio sectors and the multiplexed AAL-2 stream have independent CU-timers. Due to the independent CU-timers a bound in the delay across the AAL-2 layer entities is guaranteed.

- 5 -

A further improvement of the described system may foresee that the CU timer used in the AAL-2 multiplexing unit has a larger value than the CU time of the parallel data streams before the multiplexing unit. By this, the probability of occupancy of the ATM cells is further increased which means that the efficiency of the bandwidth usage is further increased.

Further advantages are related to the subclaims.

It is emphasized that because of the fact that the system mentioned above is based on variable bit rated data processing, the bandwidth of each channel corresponding to a respective termination point of the base station may vary notwithstanding the fact that the system is still capable of processing the data as described above.

The invention is now illustrated by means of an embodiment as depicted in the drawings.

Fig. 1 shows a general set up of a telecommunication network according to the prior art

Fig. 2 shows a detail of Fig. 1 directed to the data processing between the base station and the radio network controller RNC

Fig. 3 shows a modification of the ATM switch unit of Fig. 2 according to the embodiment of the present invention

Fig. 4 illustrates the functional principles of the present invention by means of a cell diagram

- 6 -

and

Fig. 5 shows the protocol stack for the multiplexing unit according to the present invention.

As can be seen from Fig. 1, in a conventional telecommunication network different base stations BS are comprised each of which defining a cell (depicted by a circle). The base stations are communicating with a central radio network controller RNC via a broadband data connection using an I_{UB} interface. Within a given cell, the identification and information of a call of a given mobile station MS is received via the antenna of a given base station, processed through a receiver in which the data are digitalized and transmitted to a termination point. From the termination point the data are transmitted to the Radio Network Controller RNC via the AAL-2 over ATM standard technology.

As also shown in Fig. 1, each cell is divided in different sectors, where as each sector has its own termination point. The division of a cell in a variety of sections is preferred for those cells which have a lot of traffic.

The data processing for a base station with a variety of sectors is shown in Fig. 2.

The calls received in the different sectors are digitalized and processed by separate units each of which having separate termination points. It is clear that the termination points are usually physically distributed, i.e. that they are located in different areas. Their distance may vary between a few centimetres up to hundreds of meters.

- 7 -

Each of the data streams leaving the termination points of the different sectors of one base station are processed in parallel and are sent to an ATM switch AXU where they are processed to the I_{UB} interface communicating with the central radio network controller RNC. The data traffic between the different termination points and the ATM switch uses a known so-called „UTOPIA“ interface.

Fig. 3 shows a block diagram of a network according to the present invention. This embodiment refers to a „Third Generation“ Telecommunication Network. Generally, it corresponds to the system as described related with Fig. 2. In contrast to that, however, between each of the parallel outgoing data lines coming from the different termination points of the base station on one hand and the ATM switch AXU on the other hand, a multiplexing unit AAM CPS MUX is comprised. In this unit the different cells coming from different base station sectors are combined into the same virtual channel of an ATM cell arriving at the ATM switch.

This process is shown in Fig. 4.

The calls received in sector 1 of a given base station are named e.g. CID-1 and CID-2 and are mapped in the AAL-2 over ATM cell coming from the termination point of sector 1. It is shown that because of the fixed length of an ATM cell some space is left free „DUMMY“ which means that an only partially filled cell is transmitted from sector 1. Accordingly, from sector 2 only one call-ID (CID-3) is transmitted which means that even more of the ATM cell is transmitted unfilled. The same refers to the calls coming from sector 3 as also shown in Fig. 4.

- 8 -

After the multiplexing process in unit AAM CPS MUX, ATM cells are transmitted which are completely filled because the space available in a given cell is filled with the remaining payload originating from another cell coming from a different radio sector. For example as shown in fig. 4, the first cell coming from sector 1 is filled up with the data coming from sector 2 (CID-3) until the first cell is filled and the rest of the information of CID-3 is mapped into the second ATM cell after which the rest of this second cell is filled with the traffic coming from sector 3. Therefore, the number of CID's used in a single ATM VCC is now significantly larger because it combines calls coming from different base stations sectors. Moreover, the dummy information contained before in the AAL-2 cells at the UTOPIA interface between the BS sectors and the multiplexing unit is removed.

Even if the time delay used for the coding of the AAL cells within the base station sectors is kept small in order to allow a low maximum delay, the occupancy rate of the ATM cell processed to the ATM switch, e.g. after multiplexing, is very high. By this the efficiency of the bandwidth usage of the system is significantly increased.

Fig. 5 shows the corresponding protocol stack for the multiplexing unit according to the present invention.

In the lower part of Fig. 5 the first three layers (PHY, ATM, CPS, AAL-2 Muxing) of the multiplexing unit are shown. These three layers are used by all instances of the upper layers, which are provided for each incoming data line individually.

The upper layers comprise the CPS AAL-2 layer and the SSC AAL-2 layer as well as radio interface protocol layers.

CLAIMS

1. Telecommunication network using the W-CDMA protocol comprising a variety of base stations (BS) communicating with each other via a central Radio Network Controller (RNC) by an ATM based data connection via an I_{UB} interface, whereby at least one of the base stations (BS) is comprising a variety of radio sectors (1,2,3,...n) with physically distributed AAL-2 based termination points (TP), each termination point having a AAL-2 over ATM structure where different call ID's are mapped into respective ATM virtual connections (ATM/VC) under the control of a control unit timer (CU-timer) having a determined delay time, all AAL cell streams being sent parallel to each other to an ATM switching unit (AXU) via an UTOPIA interface,
characterized in, that the ATM switching unit comprises a multiplexing unit (AAM CPS MUX) for multiplexing AAL-2 connections of the different termination points (TP) into one single ATM virtual connection to be processed by the ATM switch.
2. Telecommunication network according to claim 1,
characterized in, that both the AAL-2 stream coming from the individual radio sectors and the multiplexed AAL-2 stream have independent CU-timers.

3. Telecommunication network according to claim 1 or 2, **characterized in**, that each of the channels of the sectors have different bandwidths.

4. Telecommunication network according to one of the proceedings claims, **characterized in**, that the multiplexing unit (AAM CPS MUX) has a switchable bypass line.

5. Telecommunication network according to claim 4, **characterized in**, that the multiplexing unit (AAM CPS MUX) is of plug-in type.

6. ATM switch for a telecommunication network using the W-CDMA protocol comprising a variety of base stations (BS) communicating with each other via a central Radio Network Controller (RNC) by an ATM based data connection via an I_{UB} interface whereby at least one of the base stations (BS) is comprising a variety of radio sectors (1,2,3,...n) with physically distributed AAL-2 based termination points, each termination point having a AAL-2 over ATM structure where different call ID's are mapped into ATM virtual connections (ATM/VC) under the control of a control unit timer (CU-timer) having a determined delay time, all AAL cell streams being sent parallel to each other to an ATM switching unit (AXU) via an UTOPIA interface, **characterized in**, that the ATM switching unit comprises a multiplexing unit (AAM CPS MUX) for multiplexing AAL-2 connections of the different termination points TP into one single ATM virtual connection to be processed by the ATM switch.

7. Method for data processing in a telecommunication network using the W-CDMA protocol, the network consisting of a variety of basis stations communicating with a central radio network controller via an I_{UB} interface in which the data connection between the base stations and the RNC controller uses ATM based broadband data traffic, whereby at least one of the base stations generates AAL over ATM data streams corresponding to the termination points of different radio sectors within one cell (base station), the different call ID's within the same sector being mapped into AAL-2 over ATM streams with a given delay time under control of a control unit timer, and whereby all ATM cell streams of the different sectors of one base unit are sent in parallel to an ATM switching unit via an UTOPIA interface, characterized in, that parallel incoming AAL-2 connections of the different termination points of one base station are multiplexed into one single ATM cell virtual connection before being processed by the ATM switch.




Fig. 1




Fig. 2




Fig. 3




Fig.4




Fig. 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/07210

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q11/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	BOLDT M ET AL: "Modeling an ATM-based access network for 3rd generation mobile communication networks" VTC '98. 48TH IEEE VEHICULAR TECHNOLOGY CONFERENCE. PATHWAY TO A GLOBAL WIRELESS REVOLUTION (CAT. NO.98CH36151), VTC '98. 48TH IEEE VEHICULAR TECHNOLOGY CONFERENCE. PATHWAY TO A GLOBAL WIRELESS REVOLUTION, OTTAWA, ONT., CANADA, 18-21 MAY 1998, pages 2590-2593 vol.3, XP002136953 1998, New York, NY, USA, IEEE, USA ISBN: 0-7803-4320-4 * sections I-IV *	1,6,7
Y	GB 2 322 515 A (NORTHERN TELECOM LTD) 26 August 1998 (1998-08-26) page 7, line 8 - line 9 page 8, line 1 - line 3 -/-	1,6,7



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

4 May 2000

Date of mailing of the international search report

18/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gregori, S

INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/EP 99/07210

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	BYUNG-HAN RYU ET AL: "Performance evaluation for low bit-rate voice traffic in IMT-2000 network" PROCEEDINGS OF IEEE. IEEE REGION 10 CONFERENCE. TENCON 99. 'MULTIMEDIA TECHNOLOGY FOR ASIA-PACIFIC INFORMATION INFRASTRUCTURE' (CAT. NO.99CH37030), PROCEEDINGS OF IEEE. IEEE REGION 10 CONFERENCE. TENCON 99. 'MULTIMEDIA TECHNOLOGY FOR ASIA-PACIFIC INF, 15 - 17 September 2000, pages 238-241 vol.1, XP002136954 1999, Piscataway, NJ, USA, IEEE, USA ISBN: 0-7803-5739-6 * sections I-IV *	1-7
A	EP 0 915 634 A (LUCENT TECHNOLOGIES INC) 12 May 1999 (1999-05-12) figure 1 column 6, line 39 - line 49 column 8, line 39 - line 54	1,6,7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/07210

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2322515 A	26-08-1998	EP 0962117 A WO 9837728 A	08-12-1999 27-08-1998
EP 0915634 A	12-05-1999	JP 11225150 A	17-08-1999